

PRODUCT INFORMATION

BUILDER BOARD™ BREATHABLE TAPE

Prevent cure lines and let vapors escape by seaming with the strong, high tack hold of Builder Board™ Breathable Tape. Promote even finishes in curing concrete, stained, refinished, epoxy coated and most other floor types with Breathable Tape, the companion roll to Builder Board™ Seam Tape. It's strong, flexible, lays flat and always **tougher than the jobsite.™**



Breathable



FEATURES

- Breathable to promote vapor escape
- Strong, high tack & flexible hold
- Specialty alternative to Builder Board Seam Tape

APPLICATIONS

- Curing concrete
- Epoxy floors
- Refinishing
- Remodeling
- Seaming Builder Board
- Temporary Protection



PRODUCT SPECIFICATIONS

Total Thickness	7.2 mil nominal
Backing	Paper non woven
Adhesive Type	Hot melt
Adhesion Weight	32 g/m ²
Tensile Strength (steel)	2.0
Cling continuation	No more than 2.5mm
Backing Weight	33-40g/m ²
Temperature (Ideal)	70° F
Humidity (Ideal)	50%
Elongation	9%
Chemical Name	n.a.
Chemical Family	Vegetable fiber, Chemical fiber
Chemical Formula	Proprietary
Trade Name	Builder Board BreathableTape
Material Use	Surface Protection

AVAILABLE SIZES

BLD072BR	White	3 in x 36 yd	8 oz.
----------	-------	--------------	-------

INSTRUCTIONS

Peel back edge of Builder Board Breathable Tape and begin to unroll. Press down edge at beginning of area to be covered so Breathable Tape adheres. Continue rolling onto area, applying firm pressure and smoothing down the film while doing so. Carefully cut end with a sharp edge. When finished, fold edge of the film back against the roll to use at a later time. Removal: roll up Builder Board Breathable Tape & discard.

HANDLING AND STORAGE

Store at room temperature and keep out of direct sunlight exposure. If Builder Board Breathable Tape is stored in extreme conditions over 95° F or below 40° F allow product to return to room temperature prior to use.

SAFETY

SDS for Surface Shields products available by request.

The information in this document was obtained from sources which we believe reliable. The information is provided without any warranty expressed or implied regarding its correctness. We do not assume responsibility for loss, damage or expense in any way connected with the handling, storage, use or disposal of the product.

© 2015 Surface Shields, Inc. All rights reserved. Product names & attributes trademark of Surface Shields, Inc. where applicable.

5102.11

CORPORATE OFFICE

10457 163RD PLACE
ORLAND PARK, ILLINOIS 60467

P 844 4NO MESS
F 708 226 9817



surfaceshields.com