

# PRODUCT INFORMATION

## CONTRACTOR GRADE DUCT TAPE

For long-term holding power, the contractor grade series Duct Tape is available. This duct tape is 11 mil thick and resists delamination. It's also great for abatement applications and is **tougher than the jobsite.**<sup>™</sup>



Heavy Duty



Liquid Shield



### FEATURES

- Long-term holding power
- Resists delamination
- Great for abatement applications
- 60 yards per roll for maximum coverage
- Easy to install - lays fast and flat

### APPLICATIONS

- Construction
- Commercial
- Remodeling
- Painting
- Industrial
- Residential



### PRODUCT SPECIFICATIONS

Thickness	11 mil
Material	PE Coated Cloth
Adhesive Type	Synthetic Rubber
Adhesion to Steel	47 oz/inch
Tensile Strength	27 lbs/in
Temperature (Ideal)	70° F
Humidity (Ideal)	50%
Elongation (%)	n.a.
Chemical Name	n.a.
Chemical Family	n.a.
Chemical Formula	Proprietary
Trade Name	Duct Tape
Material Use	Surface Protection

### AVAILABLE SIZES

DCG48S	Silver	2" x 180'	n.a.
DCG398S	Silver	2" x 180'	n.a.
DCG48B	Black	2" x 180'	n.a.
DCG48R	Red	2" x 180'	n.a.

### INSTRUCTIONS

Apply as needed. Remove slowly from surface.

### HANDLING AND STORAGE

No special handling requirements. Store at room temperature, protect as needed. Always test before use. For best results, remove tape slowly at 90 degree angle, when finished applying.

### SAFETY

SDS sheets for Surface Shields products available by request.

*The information in this document was obtained from sources which we believe reliable. The information is provided without any warranty expressed or implied regarding its correctness. We do not assume responsibility for loss, damage or expense in any way connected with the handling, storage, use or disposal of the product.*

© 2015 Surface Shields, Inc. All rights reserved. Product names & attributes trademark of Surface Shields, Inc. where applicable.

5102.70

#### CORPORATE OFFICE

10457 163RD PLACE  
ORLAND PARK, ILLINOIS 60467

P 844 4NO MESS  
F 708 226 9817



[surfaceshields.com](http://surfaceshields.com)