

PRODUCT INFORMATION

POLYETHYLENE FILM TAPE

Polyethylene film coated with a high tack synthetic rubber adhesive. Recommended for masking surfaces on outdoor stucco applications. Maintains a watertight seal in all weather conditions. Available with clean edge or serrated edges for easy tear.



Heavy Duty



Liquid Shield



FEATURES

- Conforms very well to all types of surfaces
- Will hold on rough surfaces
- Moisture resistant
- Excellent low temperature bonding
- Good tear characteristics

APPLICATIONS

- Construction
- Commercial
- Remodeling
- Stucco
- Painting
- Patching
- Industrial
- Residential



PRODUCT SPECIFICATIONS

Thickness	7 mil
Material	Polyethylene
Adhesive Type	Synthetic Rubber
Adhesion	60 oz/inch
Tensile Strength	18 lbs/in
Temperature (Ideal)	70° F
Humidity (Ideal)	n.a.
Elongation	70%
Chemical Name	n.a.
Chemical Family	n.a.
Chemical Formula	Proprietary
Trade Name	Polyethylene Tape
Material Use	Surface Protection

AVAILABLE SIZES

PETR2180C	Red	2" x 180'	1 lb.
PETW2180C	White	2" x 180'	1 lb.
PETR4180C	Red	4" x 180'	2 lbs.
PETW4180C	White	4" x 180'	2 lbs.

INSTRUCTIONS

Apply as needed. Remove slowly from surface.

HANDLING AND STORAGE

No special handling requirements. Store at room temperature, protect as needed. Always test before use.

SAFETY

SDS sheets for Surface Shields products available by request.

The information in this document was obtained from sources which we believe reliable. The information is provided without any warranty expressed or implied regarding its correctness. We do not assume responsibility for loss, damage or expense in any way connected with the handling, storage, use or disposal of the product.

© 2015 Surface Shields, Inc. All rights reserved. Product names & attributes trademark of Surface Shields, Inc. where applicable.

5102.70

CORPORATE OFFICE

10457 163RD PLACE
ORLAND PARK, ILLINOIS 60467

P 844 4NO MESS
F 708 226 9817



surfaceshields.com