

PRODUCT INFORMATION

QUICK SHIELD™

The perfect tool to protect carpeting along trim and baseboards, Quick Shield™ is easy to use and peels off cleanly, without leaving any residue. Use it to hold down tarps or on it's own, it's the most convenient solution to protect against paint drips, spills, construction dust, dirt and moisture.



Liquid Shield



Recyclable



FEATURES

- Self-adhering film that goes down fast
- Helps protect carpets most at risk areas, along baseboards and near walls
- Protects carpeting from paint drips, spills, construction dust, dirt and moisture
- Highly resistant to tears and punctures
- Protects all types of carpeting for up to 30 days

APPLICATIONS

- Construction
- Moving
- Remodeling
- Model Homes
- Drywall
- Painting
- Parties
- Temporary Protection



PRODUCT SPECIFICATIONS

Thickness	2.5 mil nominal
Film	Low Density Polyethylene
Adhesive Type	Formulated Acrylic
Adhesion Level	17-25 oz/in
Tensile Strength	3000 psi
Temperature (Ideal)	70° F
Humidity (Ideal)	50%
Elongation MD	600%
Chemical Name	Acrylic PSA Tapes
Chemical Family	Acrylic PSA Polyethylene Film
Chemical Formula	Proprietary
Trade Name	Quick Shield™
Material Use	Surface Protection

AVAILABLE SIZES

QSKIT	Clear	9" x 50'	Roller & 2 rolls	3 lbs.
QS9100	Clear	9" x 100'	12 pack	12 lbs.

INSTRUCTIONS

Peel back edge of Quick Shield™ and begin to unroll. Press down edge at beginning of area to be covered so Quick Shield™ adheres. Continue rolling onto carpet, applying pressure and smoothing down the film while doing so. Carefully cut end with a sharp edge. When finished, fold edge of the film back against the roll to use at a later time. Removal: roll up Quick Shield™ and discard.

HANDLING AND STORAGE

Do not apply to hardwood floors or other hard surfaces. Always test Quick Shield™ on a small portion of carpet that is in a non-exposed area. 72 hour test required for use over adhesive installations. Temporary protection for up to 30 days. Recommended for synthetic carpeting only. Apply only to dry carpet, do not use under damp conditions.

SAFETY

SDS sheets for Surface Shields products available by request.

The information in this document was obtained from sources which we believe reliable. The information is provided without any warranty expressed or implied regarding its correctness. We do not assume responsibility for loss, damage or expense in any way connected with the handling, storage, use or disposal of the product.

© 2015 Surface Shields, Inc. All rights reserved. Product names & attributes trademark of Surface Shields, Inc. where applicable.

5102.70

CORPORATE OFFICE

10457 163RD PLACE
ORLAND PARK, ILLINOIS 60467

P 844 4NO MESS
F 708 226 9817



surfaceshields.com