

PRODUCT INFORMATION

WINDOW SHIELD

Protect windows against mortar stains, stucco, over sprays, residue and more with the easy to apply Window Shield. Formulated never to leave a residue, this protective film is available in short, medium and long term protection, ranging from 45 days to 1 year. Start saving time and money on the job with this dependable window film.



Liquid Shield



Recyclable



FEATURES

- Self-adhering protective film for windows and glass
- Protects against over-sprays, mortar stains and stucco
- No more scraping and cleaning damage to the glass
- Saves time, labor and money

APPLICATIONS

- Construction
- Remodeling
- Tuck Pointing
- Drywall
- Painting
- Temporary Protection



PRODUCT SPECIFICATIONS

Thickness	1.5 mil nominal (short term) 3.1 mil nominal (long term)
Film	Polyethylene (short term), PVC w/UV Inhibitor (long term)
Adhesive Type	Water-based Acrylic
Adhesion Level	8.5 oz/in (short term), 48 oz/in (long term)
Tensile Strength	2-3000 psi (short term), 5100 psi (long term)
Temperature (Ideal)	70° F
Humidity (Ideal)	50%
Elongation	300-400% (short term), 260% (long term)
Chemical Name	Acrylic PSA Tapes
Chemical Family	Acrylic PSA Polyethylene Film
Chemical Formula	Proprietary
Trade Name	Window Shield
Material Use	Surface Protection

AVAILABLE SIZES

W2B12600	Blue	12in x 600ft (30-45 days, 2pk)
W2B24250	Blue	24in x 250ft (30-45 days)
W2B24600	Blue	24in x 600ft (30-45 days)
W2C24600	Clear	24in x 600ft (30-45 days)
W2C36250	Clear	36in x 250ft (30-45 days)
W3C24600	Clear	24in x 600ft (90-180 days)
W4B24330	Blue	24in x 330ft PVC Long term (6mns -1yr)
W4B36330	Blue	36in x 330ft PVC Long term (6mns -1yr)

INSTRUCTIONS

Always test before use. Peel back edge of Window Shield and begin to unroll. Press down edge at beginning of area to be covered so Window Shield adheres. Continue rolling onto area, applying pressure and smoothing down the film while doing so. Carefully cut end with a sharp edge. When finished, fold edge of the film back against the roll to use at a later time. Removal: roll up Window Shield and discard.

HANDLING AND STORAGE

Store at room temperature and keep out of direct sunlight exposure. If Window Shield is stored in extreme conditions over 95° F or below 40° F allow product to return to room temperature prior to use.

SAFETY

SDS for Surface Shields® products available by request.

The information in this document was obtained from sources which we believe reliable. The information is provided without any warranty expressed or implied regarding its correctness. We do not assume responsibility for loss, damage or expense in any way connected with the handling, storage, use or disposal of the product.

© 2016 Surface Shields, Inc. All rights reserved. Product names & attributes trademark of Surface Shields, Inc. where applicable.

6102.10

CORPORATE OFFICE

8450 185TH ST.
TINLEY PARK, IL 60487

P 844 4NO MESS
F 708 226 9817




surfaceshields.com

! "#\$%&'()*+,-./01#2%-340%#5'1#60-. /0%#6'7! 4--4#085'9: : +"/40%#'

Product Information and Limited Warranty

Please Read this Important Information on General Conditions for Application and Use of Window Shield™

Before using, the purchaser and/or user must determine suitability of this product for the intended use and the purchaser and/or user assumes all risks and liabilities in connection therewith. To determine suitability, test Window Shield™ on a small portion of one window or glass surface. For applications intended to exceed a 10-day period, leave Window Shield™ in place for at least 10 days and then inspect the surface where the product was applied to ensure the product is suitable for your application. On applications intended for less than a 10-day period, test Window Shield prior to full application on one window or glass surface for the desired application length to determine suitability.



- ! "#\$%&'()*+,-./0123456789:;@A B C D E F G H I J K L M N O P Q R S T U V W X Y Z [\] ^ _ ` a b c d e f g h i j k l m n o p q r s t u v w x y z { | } ~ ¡ ¢ £ ¤ ¥ ¦ § ¨ © ª « ¬ ® ¯ ° ± ² ³ ´ µ ¶ · ¸ ¹ º » ¼ ½ ¾ ¿
- 8*(2*)(" --\$.)*("2. (4%&1"'+ (*)O' &O"2(3\$"44(/#26*/4(*&(3\$"44(4%&1"'+ 4(
- 9\$/". 4(" --\$. (: #26*/(: O# \$6<(*2("+' "2=6&. (4%&1"'+ (*2\$. <
- 9\$/". 4O' 4): #26*/(: O# \$6<(*2("4, "§(-*&)*2(*2'(/#26*/(*&(3\$"44(4%&1"'+)*(6')' &, #2' (4%#)"?#&#). <
- !*&(" --\$#+"")#*24(#2)' 26' 6O'*('@+' ' 6("ABC6". (-' &#*6= ("ABC6". O' 4)(#4(& D%#&' 6(1*&(%4' (-&#*&O'*(1%§§(" --\$#+"")#*2()*(6')' &, #2' (4%#)"?#&#). <(E2(" --\$#+"")#*24(#2)' 26' 6(1*&(\$ 44O"2("ABC6". (-' &#*6=O' 4): #26*/(: O# \$6(-&#*&O'*(1%§§(" --\$#+"")#*2(*2'(/#26*/(*&(3\$"44(4%&1"'+ (1*&O' (6' 4#&' 6(" --\$#+"")#*2(\$ 23)O'*(6')' &, #2' (4%#)"?#&#). <
- !*&O', -*&"&. (%4' (*2\$. (F&' , *5' (*&(&' -\$'+ (/#)O(2' /(: #26*/(: O# \$6<(*2(*&(?' 1*&' O' (+, -\$')#*2(*1(GB(6". 4(*1(" --\$#+"")#*2<
- H(4%?1'+) 6O'*('@&' , ' (/ ' ")O' &(+*26#)#*24(*1O' , -' &")%&' 4('@+' ' 6#23(JKL(!(*&(6#&' +)=#2)' 24' (4%2\$#30)(1*&(' @' 26' 6(-' &#*64(*1O)#, '=#)(#4(&' +*, , ' 26' 6(: #26*/(: O# \$6<(1#\$, (?' (#24-' +)' 6("26(&' -\$'+ 6(/#)O(2' / (, ")' &#*\$, *&' (1& D% 2)\$.("26("4(2' ' 6' 6<
- M\$ "4' (& 5# /(-&*6%+)(#21*&, ")#*2= (#24)&#)+#*24= (/""&"2). ("26(" --\$#+"")#*2(#21*(?' 1*&' (%4' <

Product Information

Before applying Window Shield™, please carefully read the following important information:

Window Shield™ is for glass windows or glass surfaces, do not apply to any other surface or allow Window Shield™ to overlap beyond the window/glass area or onto hard surfaces such as wood, vinyl or aluminum. Use only on a completely dry surface. If subjected to extreme conditions of temperatures exceeding 95° F or direct, intense sunlight for extended periods of time, it is recommended Window Shield™ film be inspected and replaced with new material more frequently and as needed. Window Shield™ is for temporary protection up to 30 days, REMOVE ON 30TH DAY or sooner.

Product Storage Guidelines

For best performance, store at room temperature and out of direct sunlight exposure. If Window Shield™ is stored in extreme conditions (over 95° F or below 40° F), allow product to return to room temperature and always test before use. Not recommended for use after three months of purchase date.

Limited Warranty

Before using, the purchaser and/or user must determine suitability of this product for the intended user and the purchaser and/or user assumes all risks and liabilities in connection therewith. The sole obligation of the manufacturer, distributor and/or seller of this product shall be the replacement of the Window Shield™ product if notified of any product defect within three months of the date of purchase. Such quantity of the product deemed defective shall be replaced or the amount of the purchase refunded and there shall be no liability to injury, loss or damages, either direct or consequential, arising out of the use or inability to use this product. The company disclaims all oral warranties of any kind. This limited warranty offered in connection with manufacture and sale of the product is exclusive and in lieu of any warranties expressed, implied or statutory, including without limitation any direct or implied warranty of merchantability or fitness for a particular use. **In the event of a claim, failure to notify the manufacturer of the incident prior to any remedy or resolution, including during the claims process, voids the warranty and the manufacturer's liability. Window cleaning prior to notifying the manufacturer of a claim voids the warranty and any liability on the part of the manufacturer.**

Easy Application Steps for Window Shield

Always complete a 10-day test if Window Shield™ is anticipated to be applied for over 10 days. On applications intended for less than a 10-day period, test Window Shield prior to full application on one window or glass surface for the desired application length to determine suitability. Only apply to window/glass surfaces. Peel back edge of Window Shield™ and unroll Window Shield™ sticky-side down on window/glass surface. Continue rolling onto area, applying pressure and smoothing down the film while doing so. Carefully cut end with a sharp edge. Ensure that edges are secure so that water will be unable to seep in during use. Removal: Roll up Window Shield™ and discard.