

DRYWALL MESH TAPE



SECTION 1: IDENTIFICATION

Product Identifier	Fiberglass Self-Adhesive Mesh Tape
Company Identification	Surface Shields® Inc 10457 163rd Place Orland Park, IL 60467 1 (844) 466 6911
Emergency Number	Dial 911
Recommended Use	To reinforce and seam drywall joints, repair holes, cracks, etc

SECTION 2: HAZARD IDENTIFICATION



Eye Contact	Eye contact not expected during normal use
Skin Contact	No health effects anticipated
Inhalation	No health effects anticipated
If Swallowed	Ingestion not expected during normal use

SECTION 3: COMPOSITION

Fiberglass	CAS No. 65997-17-3, 64-74%, 15/5(R) OSHA PEL
Acrylic Acid	N/A, N/A, N/A, N/A
Acrylate Copolymer	N/A, 26-36%, N/A, N/A

SECTION 4: FIRST-AID MEASURES

Eye Contact	Flush eyes with water for at least 10 minutes; get medical assistance if irritation persists
Skin Contact	Wash with soap & water
Inhalation	Drink water to clear throat & blow nose to expel fibers
If Swallowed	Contact emergency services
In Case of Emergency	Dial 911

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Methods	Water Spray, Carbon Dioxide, Dry Chemical, Foam
Special Procedures	Breathing apparatus
Unusual Fire Hazards	Product will not burn

SECTION 6: ACCIDENTAL RELEASE MEASURES

Precautions	Not applicable, material is solid
-------------	-----------------------------------

SECTION 7: HANDLING AND STORAGE

Handling Precautions	Provide adequate ventilation
Safe Storage	Store in cool, dry place

SECTION 8: EXPOSURE CONTROLS

Respiratory Protection	Where dust levels exceed TLV, use NIOSH approved respirator
Ventilation	Mechanical or local exhaust to keep below TLV
Protective Equipment	Gloves, safety glasses

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Freeze-thaw Stability	-10° C (adhesive)
SRV (%)	52±1%(adhesive)
Melting Point	1100° C (fiberglass)
Appearance & odor	Woven fabric, coated, white; slight hydrocarbon odor
Vapor Pressure	N/A
Vapor Density	N/A
Softening Point	31-33° C (adhesive)
Specific Gravity	1.95-2.1 (H ₂ O=1)
Solubility	Insoluble in water

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability	Yes
Other	N/A

SECTION 11: TOXICOLOGICAL INFORMATION

Other	This coating resin may contain trace amounts of formaldehyde. Formaldehyde is identified by ACGIT, OSHANTP and IARC as a potential carcinogen. Formaldehyde has been shown to cause mutations in a variety of in-vitro test systems. There should be minimal risk when used with ventilation adequate to keep the atmospheric concentration below the recommended exposure limit.
-------	---

SECTION 13: DISPOSAL CONSIDERATIONS

Other	In most cases, woven fiberglass scrap can be disposed of in a sanitary landfill in accordance with federal, state and local regulations.
-------	--

SECTION 16: OTHER INFORMATION

SDS Prepared	June 2015
Latest Revision	October 2016

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warranties or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.