

PRODUCT INFORMATION

DOUBLE SIDED TAPE

This general purpose double sided tape is designed for mounting, splicing and joining. Perfect for on-the-job or around the house, Surface Shields double sided tape is nearly 3 mil thick with a paper release liner, and has a rubber based adhesive.



Heavy Duty



FEATURES

- High grade synthetic Hot Melt Rubber Adhesive
- Tough white siliconized paper release liner
- 2.1mil (55 micron) non-oriented Polypropylene Film

APPLICATIONS

- Splicing
- Holding / Joining
- Mounting / Laminating
- High stretch for curved surfaces
- Great tack for smooth / rough textured surfaces



PRODUCT SPECIFICATIONS

Backing	2.2mil (0.055mm) White BOPP film
Adhesive	Synthetic Hot Melt Rubber
Total Thickness	4.4mil (0.110) exclusive of liner
Liner Thickness	2.1mil
Adhesion to SST	70.6oz/inch
Tensile Strength	5lb/inch
Elongation	800% at break

AVAILABLE SIZES

DST275C	White Paper Liner	2in x 75ft
---------	-------------------	------------

INSTRUCTIONS

Apply as needed. Remove slowly from surface.

HANDLING AND STORAGE

No special handling requirements. Store at room temperature, protect as needed. Always test before use. Recommended shelf life one year when stored at 64-70 degrees fahrenheit, 50% relative humidity. Keep out of direct sunlight.

SAFETY

SDS for Surface Shields products available by request.

The information in this document was obtained from sources which we believe reliable. The information is provided without any warranty expressed or implied regarding its correctness. We do not assume responsibility for loss, damage or expense in any way connected with the handling, storage, use or disposal of the product.

© 2016 Surface Shields, Inc. All rights reserved. Product names & attributes trademark of Surface Shields, Inc. where applicable.

6102.60

CORPORATE OFFICE

10457 163RD PLACE
ORLAND PARK, ILLINOIS 60467

P 844 4NO MESS
F 708 226 9817



surfaceshields.com